NSN 5320-01-375-9815

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-375-9815

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.940 inches and 0.960 inches

Head Style:

Flush countersunk

Width Between Flats:

Between 0.0791 inches and 0.0806 inches

Shank Diameter:

Between 0.2177 inches and 0.2182 inches

Shank Style:

Head Major Diameter:

Between 0.3253 inches and 0.3303 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

Grip Length:

Between 0.620 inches and 0.630 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

2000 pounds per square inch

Thread Size:

0.190 inches

Shear Strength:

7100 double pounds per square inch

Countersink Angle:

100.0 degrees

Special Features:

Surface coating hi-shear specification 306 type 1, color blue

Material:

Titanium alloy

Material Specification:

Ams 4928 assn standard single material response or asm 4967 assn standard single material response

Thread Series Designator:

Unjf

Specification Data:

73197-hl411vf-6-10 manufacturers standard

Shelf Life:

N/a



NSN 5320-01-375-9815

Pin-rivet - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A528u0

