

View Online at <https://aerobasegroup.com/nsn/5320-01-375-9825>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 0.760 inches and 0.780 inches

**Head Style:**

Flush countersunk

**Width Between Flats:**

Between 0.0947 inches and 0.0967 inches

**Shank Diameter:**

Between 0.2802 inches and 0.2807 inches

**Shank Style:**

Pin-riquet, straight, threaded

**Head Major Diameter:**

Between 0.5018 inches and 0.5066 inches

**Lubrication:**

Cetyl alcohol, specification 305, hi-shear corp

**Grip Length:**

Between 0.370 inches and 0.380 inches

**Thready Qty Per Inch (tpi):**

28

**Min. Tensile Strength (psi):**

5820 pounds per square inch

**Thread Size:**

0.250 inches

**Shear Strength:**

11800 double pounds per square inch

**Countersink Angle:**

100.0 degrees

**Special Features:**

Surface coating hi-shear specification 306 type 1, color blue

**Material:**

Titanium alloy

**Material Specification:**

Ams 4928 assn standard single material response or asm 4967 assn standard single material response

**Thread Series Designator:**

Unjf

**Specification Data:**

73197-hl413vf-8-6 manufacturers standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0