NSN 5320-01-376-0863

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-376-0863 **Thread Class:** За **Thread Direction:** Right-hand **Identification Code Color: Bronze Fastener Length:** Between 1.197 inches and 1.217 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.0947 inches and 0.0967 inches **Shank Diameter:** Between 0.2485 inches and 0.2495 inches **Shank Style: Head Major Diameter:** Between 0.3898 inches and 0.3948 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** Between 0.807 inches and 0.817 inches **Thread Size:** 0.250 inches **Shear Strength:** 9300 double pounds per square inch **Countersink Angle:** 100.0 degrees **Special Features:** Furnished with stainless steel threaded (break off) type collar. Steel comp e4340 body or steel comp 4140 body or steel comp 8740 body **Material Specification:** Mil-s-5000 military specification 1st material response body or mil-s-5626 military specification 2nd material response body or mil-s-6049 military specification 3rd material response body **Surface Treatment:** Cadmium body **Surface Treatment Specification:**

Unjf

Shelf Life:

Thread Series Designator:

Qq--p-416, type ii, class2 federal specification single treatment response body

N/a

NSN 5320-01-376-0863

Pin-rivet - Page 2 of 2



Unit Of Mea	sure:
-------------	-------

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-5000 spec.