NSN 5320-01-377-6230

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-377-6230 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.910 inches and 1.930 inches **Head Style:** Err-090 **Head Height:** Between 0.130 inches and 0.140 inches **Shank Diameter:** Between 0.373 inches and 0.374 inches **Shank Style:** Pin-rivet, tapered, threaded **Head Major Diameter:** Between 0.530 inches and 0.565 inches **Tip Diameter:** Between 0.364 inches and 0.368 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** Between 1.370 inches and 1.380 inches **Thread Size:** 0.375 inches **Shear Strength:** 21000 double pounds per square inch Material: Steel comp 4140 or steel comp 8740 **Material Specification:** Mil-s-5626 military specification 1st material response or mil-s-6049 military specification 2nd material response **Surface Treatment:** Chromate and cadmium **Surface Treatment Specification:** Qq-p-416 type 2 cl 2 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5320-01-377-6230

Pin-rivet - Page 2 of 2



Fiig:

A528u0

Mil-std (military Standard):

Mil-s-5626 spec.