NSN 5320-01-377-6230

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-377-6230



Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 1.910 inches and 1.930 inches

Head Style:

Err-090

Head Height:

Between 0.130 inches and 0.140 inches

Shank Diameter:

Between 0.373 inches and 0.374 inches

Shank Style:

Pin-rivet, tapered, threaded

Head Major Diameter:

Between 0.530 inches and 0.565 inches

Tip Diameter:

Between 0.364 inches and 0.368 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

Grip Length:

Between 1.370 inches and 1.380 inches

Thread Size:

0.375 inches

Shear Strength:

21000 double pounds per square inch

Material:

Steel comp 4140 or steel comp 8740

Material Specification:

Mil-s-5626 military specification 1st material response or mil-s-6049 military specification 2nd material response

Surface Treatment:

Chromate and cadmium

Surface Treatment Specification:

Qq-p-416 type 2 cl 2 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

NSN 5320-01-377-6230

Pin-rivet - Page 2 of 2

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-5626 spec.

