## NSN 5320-01-380-6159

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-380-6159



#### Thread Class:

3a

**Thread Direction:** 

**Right-hand** 

#### Fastener Length:

Between 1.377 inches and 1.397 inches

#### Head Style:

Err-090

#### Head Height:

Between 0.064 inches and 0.074 inches

#### Width Between Flats:

Between 0.0791 inches and 0.0806 inches

#### Shank Diameter:

Between 0.1890 inches and 0.1895 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.357 inches and 0.377 inches

#### Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

#### Grip Length:

Between 1.057 inches and 1.067 inches

#### Thready Qty Per Inch (tpi):

32

#### Min. Tensile Strength (psi):

3180 pounds per square inch

#### Thread Size:

0.190 inches

#### Shear Strength:

5380 double pounds per square inch

#### **Special Features:**

Surface coating hi-shear specification 305, type 1, color blue

#### Material:

Titanium alloy uns r56400

#### **Material Specification:**

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

### **Thread Series Designator:**

Unjf

#### **Specification Data:**

73197-hl12vf-6-17 manufacturers standard

#### Shelf Life:

N/a

# NSN 5320-01-380-6159

Pin-rivet - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A528u0

