

View Online at <https://aerobasegroup.com/nsn/5320-01-381-1479>

Fastener Length:

0.732 inches

Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

Shank Diameter:

Between 0.178 inches and 0.180 inches

Shank Style:

Threaded self-plugging shank w/sleeve

Head Major Diameter:

Between 0.277 inches and 0.283 inches

Expansion Device:

Threaded stem

Lubrication:

Dry film or paraffin wax or cetyl alcohol

Grip Length:

Between 0.282 inches and 0.344 inches

Features Provided:

Drive nut

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Special Features:

Drive nut mild steel, color blue with corrosion retardent coating.

Material:

Steel comp 4140 stem or steel comp 8740 stem or steel comp 4130 stem

Material Specification:

Qq-a-225/9 federal specification single material response nut

Surface Treatment:

Passivate sleeve and cadmium sleeve or passivate sleeve and cadmium sleeve and chromate sleeve

Surface Treatment Specification:

Qq-p-35 federal specification 1st treatment response sleeve and qq-p-416 federal specification 1st treatment response sleeve or qq-p-35 federal specification 2nd treatment response sleeve and qq-p-416 federal specification 2nd treatment response sleeve

Specification Data:

80205-nas1754 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-s-5626 spec.