## NSN 5320-01-381-1519

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-381-1519

Fastener Length:
1.200 inches
Head Style:
Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)
Shank Diameter:
Between 0.2575 inches and 0.2595 inches
Shank Style:
Threaded self-plugging shank w/sleeve
Head Major Diameter:
0.463 inches
Expansion Device:
Threaded stem
Lubrication:
Paraffin wax or cetyl alcohol or dry film
Grip Length:
Between 0.450 inches and 0.500 inches
Countersink Angle:
Between 129.0 degrees and 131.0 degrees
Special Features:
C in p/n is a special lubricant and finish as per specification mbf 2002.
Material:
Titanium alloy nut or titanium alloy uns r56400 nut
Material Specification:
Mil-t-9047 military specification 1st material response nut or ams4928 assn standard 2nd material response nut or ams4967 assn standard
3rd material response nut
Surface Treatment:
Passivate stem
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response stem
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A040a0
Mil-std (military Standard):
Mil-t-9047 spec.