

View Online at <https://aerobasegroup.com/nsn/5320-01-382-0084>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.885 inches and 0.905 inches

Head Style:

Flush countersunk

Width Between Flats:

Between 0.0947 inches and 0.0967 inches

Shank Diameter:

Between 0.2646 inches and 0.2651 inches

Shank Style:

Pin-riquet, straight, threaded

Head Major Diameter:

Between 0.3898 inches and 0.3948 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

Grip Length:

Between 0.495 inches and 0.505 inches

Thready Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

3700 pounds per square inch

Thread Size:

0.250 inches

Shear Strength:

10490 double pounds per square inch

Countersink Angle:

100.0 degrees

Special Features:

Surface coating hi-shear specification 305 type 1, color blue

Material:

Titanium alloy

Material Specification:

Ams 4928 assn standard single material response or asm 4967 assn standard single material response

Thread Series Designator:

Unjf

Specification Data:

73197-hl111vf-8-11 manufacturers standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A528u0