

View Online at <https://aerobasegroup.com/nsn/5320-01-383-8877>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 2.1350 inches and 2.1500 inches

**Head Style:**

Err-090

**Head Height:**

Between 0.0800 inches and 0.0900 inches

**Width Between Flats:**

Between 0.0947 inches and 0.0967 inches

**Shank Diameter:**

Between 0.2485 inches and 0.2495 inches

**Shank Style:**

Pin-rivet, straight, threaded

**Head Major Diameter:**

Between 0.4150 inches and 0.4440 inches

**Lubrication:**

Cetyl alcohol

**Grip Length:**

Between 1.7450 inches and 1.7550 inches

**Thready Qty Per Inch (tpi):**

28

**Min. Tensile Strength (psi):**

210000 pounds per square inch

**Thread Size:**

0.2500 inches

**Shear Strength:**

210000 single pounds per square inch

**Material:**

Nickel alloy 718

**Material Specification:**

Ams 5662 assn standard single material response

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Q-p-416, type 2, cl 2 federal specification 13th treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0