

View Online at <https://aerobasegroup.com/nsn/5320-01-383-9071>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.7225 inches and 0.7425 inches

Head Style:

Err-090

Head Height:

Between 0.1300 inches and 0.1400 inches

Width Between Flats:

Between 0.1582 inches and 0.1617 inches

Shank Diameter:

Between 0.3735 inches and 0.3745 inches

Shank Style:

Pin-riquet, straight, threaded

Head Major Diameter:

Between 0.5650 inches and 0.6000 inches

Lubrication:

Cetyl alcohol

Grip Length:

Between 0.1825 inches and 0.1925 inches

Thread Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

210000 pounds per square inch

Thread Size:

0.3750 inches

Shear Strength:

125000 single pounds per square inch

Material:

Nickel alloy 718

Material Specification:

Ams 5662 assn standard single material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A528u0