

View Online at <https://aerobasegroup.com/nsn/5320-01-384-5388>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.490 inches and 0.510 inches

Head Style:

Err-090

Head Height:

Between 0.055 inches and 0.065 inches

Width Between Flats:

Between 0.0791 inches and 0.0801 inches

Shank Diameter:

Between 0.1630 inches and 0.1635 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.306 inches and 0.322 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

Grip Length:

Between 0.183 inches and 0.193 inches

Min. Tensile Strength (psi):

2940 pounds per square inch

Thread Size:

0.164 inches

Shear Strength:

5280 double pounds per square inch

Special Features:

Grit blast top of head, with color green on thread end.

Material:

Nickel alloy 718

Material Specification:

Ams5662 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Hi-shear spec. 258, 73197 mfr ref single treatment response

Thread Series Designator:

Unjc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0