NSN 5320-01-384-9536

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-384-9536 **Thread Class:** За **Thread Direction:** Right-hand **Identification Code Color:** Green **Fastener Length:** Between 1.065 inches and 1.085 inches **Head Style:** Err-090 **Head Height:** Between 0.064 inches and 0.074 inches Width Between Flats: Between 0.0791 inches and 0.0806 inches **Shank Diameter:** Between 0.1890 inches and 0.1895 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.357 inches and 0.377 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** Between 0.745 inches and 0.755 inches Min. Tensile Strength (psi): 210000 pounds per square inch **Thread Size:** 0.190 inches **Shear Strength:** 125000 single pounds per square inch Material: Nickel alloy 718 **Material Specification:** Ams 5662 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Spec 258, cagec 73197 mfr ref single treatment response **Thread Series Designator:** Unjf Shelf Life:

N/a

NSN 5320-01-384-9536

Pin-rivet - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A528u0