NSN 5320-01-387-3698

Blind Rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-387-3698

Thread Class
Thread Class:
2a
Thread Direction:
Right-hand
Fastener Length:
0.885 inches
Head Style:
Hexagon
Head Height:
0.107 inches
Shank Diameter:
0.201 inches
Shank Style:
Threaded self-plugging shank w/sleeve
Expansion Device:
Expander and threaded stem
Lubrication:
Carbo wax or cetyl alcohol or paraffin wax
Grip Length:
0.450 inches
Width Across Flats:
0.309 inches
Thready Qty Per Inch (tpi):
40
Min. Tensile Strength (psi):
2100 pounds per square inch
Thread Size:
0.130 inches
Shear Strength:
9000 double pounds per square inch
Material:
Steel comp 4130 nut or steel comp 4140 nut or steel comp 8740 nut
Material Specification:
Qq-s-763 federal specification single material response sleeve
Surface Treatment:
Cadmium sleeve or passivate sleeve
Surface Treatment Specification:
Qq-p-416, type 11, class 2 federal specification 2nd treatment response nut
Thread Series Designator:
Unf
Shelf Life:
N/a

NSN 5320-01-387-3698

Blind Rivet - Page 2 of 2



		eas	

--

Demilitarization:

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-s-6758 spec.