

View Online at <https://aerobasegroup.com/nsn/5320-01-387-9905>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Fastener Length:**

0.965 inches

**Head Style:**

Hexagon

**Head Height:**

0.107 inches

**Shank Diameter:**

0.201 inches

**Shank Style:**

Threaded self-plugging shank w/sleeve

**Expansion Device:**

Expander and threaded stem

**Lubrication:**

Carbo wax or cetyl alcohol or paraffin wax

**Grip Length:**

0.470 inches

**Width Across Flats:**

0.309 inches

**Thready Qty Per Inch (tpi):**

40

**Min. Tensile Strength (psi):**

2850 pounds per square inch

**Thread Size:**

0.130 inches

**Shear Strength:**

10500 double pounds per square inch

**Material:**

Steel comp 4130 nut or steel comp 4140 nut or steel comp 8740 nut

**Material Specification:**

Qq-s-763 federal specification single material response sleeve

**Surface Treatment:**

Cadmium sleeve or passivate sleeve

**Surface Treatment Specification:**

Qq-p-416, type 11, class 2 federal specification 2nd treatment response nut

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A040a0

**Mil-std (military Standard):**

Mil-s-6758 spec.