NSN 5320-01-388-3800

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-388-3800

Fastener Length: 0.719 inches Head Style: Tapered pan Head Height: Between 0.130 inches and 0.140 inches Shank Diameter: Between 0.130 inches and 0.260 inches Shank Style: Self-plugging mechanically locked stem Head Major Diameter: Between 0.400 inches and 0.432 inches Expansion Device: Serrated stem-type w Grip Langth: Between 0.469 inches and 0.532 inches Special Features: Single action fastener installed with a single action tool Material: Iron alloy 660 mechanical lock or steel comp 316 mechanical lockiron alloy 660 sleeveiron alloy 660 stem Material Specification: Ams 5737 assn standard 1st material response mechanical lock or ams 5690 assn standard 2nd material response mechanical lockams 5737 assn standard single material response sleeveams 5737 assn standard single material response stem Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Shef Lite: N/a Unit Of Measure: Demilitarization: No Fig: A040a0 Mil-std (military Standard): Mil-fe975 spec.	
Head Height: Setween 0.130 inches and 0.140 inches Shank Diameter: Between 0.258 inches and 0.260 inches Shank Shyle: Between 0.258 inches and 0.260 inches Shank Slyle: Between 0.400 inches and 0.432 inches Self-plugging mechanically locked stem Head Major Diameter: Between 0.400 inches and 0.432 inches Expansion Device: Serrated stem-type w Grip Length: Between 0.469 inches and 0.532 inches Special Features: Single action fastener installed with a single action tool Material: Iron alloy 660 mechanical lock or steel comp 316 mechanical lockiron alloy 660 sleeveiron alloy 660 stem Material Specification: Ams 5737 assn standard 1st material response mechanical lock or ams 5690 assn standard 2nd material response mechanical lockams 5737 assn standard single material response sleeveams 5737 assn standard single material response stem Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Sheft Life: Via Unit Of Measure: Uniti Of Measure: Demilitarization: No Fig: A04080 Mil-setd (military Standard):	Fastener Length:
Tapered pan Head Height: Between 0.130 inches and 0.140 inches Shank Diameter: Between 0.258 inches and 0.260 inches Shank Styte: Self-plugging mechanically locked stem Head Major Diameter: Between 0.400 inches and 0.432 inches Expansion Device: Sorrated stem-type w Grip Length: Between 0.469 inches and 0.532 inches Special Features: Single action fastener installed with a single action tool Material: Iron alloy 660 mechanical lock or steel comp 316 mechanical lockiron alloy 660 sleeveiron alloy 660 stem Material Specification: Arns 5737 assn standard 1st material response mechanical lock or ams 5690 assn standard 2nd material response mechanical lockams 5737 assn standard single material response sleeveams 5737 assn standard single material response stem Surface Treatment: Passivate Surface Treatment Specification: Qq-p-36 federal specification single treatment response Shelf Life: Na Unit Of Measure: — Demilitarization: No Fig: A040a0 Mil-std (military Standard):	0.719 inches
Head Height: Between 0.130 inches and 0.140 inches Shank Diameter: Between 0.258 inches and 0.260 inches Shank Style: Self-plugging mechanically locked stem Head Major Diameter: Between 0.400 inches and 0.432 inches Expansion Device: Serraled stem-type w Grip Length: Between 0.400 inches and 0.532 inches Expansion Device: Serraled stem-type w Grip Length: Between 0.489 inches and 0.532 inches Special Features: Single action fastener installed with a single action tool Material: Iron alloy 660 mechanical lock or steel comp 316 mechanical lockiron alloy 660 sleeveiron alloy 660 stem Material Specification: Ams 5737 assn standard st material response mechanical lock or ams 5690 assn standard 2nd material response mechanical lock ans 5737 assn standard single material response sleeveams 5737 assn standard single material response stem Surface Treatment: Passivale Surface Treatment Specification: Qu-p-35 federal specification single treatment response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A040a0 Mil-std (military Standard):	Head Style:
Between 0.130 inches and 0.140 inches Shank Diameter: Between 0.258 inches and 0.260 inches Shank Style: Self-plugging mechanically locked stem Head Major Diameter: Between 0.400 inches and 0.432 inches Expansion Device: Serrated stem-type w Grip Length: Between 0.469 inches and 0.532 inches Special Features: Single action fastener installed with a single action tool Material: Iron alloy 660 mechanical lock or steel comp 316 mechanical lockiron alloy 660 sleeveiron alloy 660 stem Material Specification: Ams 5737 assn standard 1st material response mechanical lock or ams 5690 assn standard 2nd material response mechanical lockams 5737 assn standard single material response sleeveams 5737 assn standard single material response stem Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Shelf Life: No Unit Of Measure: Demilitarization: No Fig: A040a0 Mil-std (military Standard):	Tapered pan
Shank Diameter: Between 0.258 inches and 0.260 inches Shank Style: Self-plugging mechanically locked stem Head Major Diameter: Between 0.400 inches and 0.432 inches Expansion Device: Serrated stem-type w Grip Length: Between 0.469 inches and 0.532 inches Special Features: Single action fastener installed with a single action tool Material: Iron alloy 660 mechanical lock or steel comp 316 mechanical lockiron alloy 660 sleeveiron alloy 660 stem Material Specification: Ams 5737 assn standard 1st material response mechanical lock or ams 5690 assn standard 2nd material response mechanical lockams 5737 assn standard single material response sleeveams 5737 assn standard single material response stem Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fitig: A040a0 Mil-std (military Standard):	Head Height:
Between 0.258 inches and 0.260 inches Shank Style: Self-plugging mechanically locked stem Head Major Diameter: Between 0.400 inches and 0.432 inches Expansion Device: Serrated stem-type w Grip Length: Between 0.469 inches and 0.532 inches Special Features: Single action fastener installed with a single action tool Material: Iron alloy 660 mechanical lock or steel comp 316 mechanical lockiron alloy 660 sleeveiron alloy 660 stem Material Specification: Ams 5737 assn standard 1st material response mechanical lock or ams 5690 assn standard 2nd material response mechanical lockams 5737 assn standard single material response sleeveams 5737 assn standard single material response stem Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A040a0 Mil-std (military Standard):	Between 0.130 inches and 0.140 inches
Shank Style: Self-plugging mechanically locked stem Head Major Diameter: Between 0.400 inches and 0.432 inches Expansion Device: Serrated stem-type w Grip Length: Between 0.469 inches and 0.532 inches Special Features: Single action fastener installed with a single action tool Material: Iron alloy 660 mechanical lock or steel comp 316 mechanical lockiron alloy 660 sleeveiron alloy 660 stem Material Specification: Arns 5737 assn standard 1st material response mechanical lock or arms 5690 assn standard 2nd material response mechanical lockards 5737 assn standard single material response stem Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Shelf Life: N/a Unit Of Measure: — Demilitarization: No Filig: A040a0 Mil-std (military Standard):	Shank Diameter:
Self-plugging mechanically locked stem Head Major Diameter: Between 0.400 inches and 0.432 inches Expansion Device: Serrated stem-type w Grip Length: Between 0.469 inches and 0.532 inches Special Features: Single action fastener installed with a single action tool Material: Iron alloy 660 mechanical lock or steel comp 316 mechanical lockiron alloy 660 sleeveiron alloy 660 stem Material Specification: Arns 5737 assn standard 1st material response mechanical lock or ams 5690 assn standard 2nd material response mechanical lockams 5737 assn standard single material response stem Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Sheff Life: Na Unit Of Measure: — Demilitarization: No Flig: A040a0 Mil-std (military Standard):	Between 0.258 inches and 0.260 inches
Head Major Diameter: Between 0.400 inches and 0.432 inches Expansion Device: Serrated stem-type w Grip Length: Between 0.469 inches and 0.532 inches Special Features: Single action fastener installed with a single action tool Material: Iron alloy 660 mechanical lock or steel comp 316 mechanical lockiron alloy 660 sleeveiron alloy 660 stem Material Specification: Ams 5737 assn standard 1st material response mechanical lock or ams 5690 assn standard 2nd material response mechanical lockams 5737 assn standard single material response sleeveams 5737 assn standard single material response stem Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig: A040a0 Mil-std (military Standard):	Shank Style:
Between 0.400 inches and 0.432 inches Expansion Device: Serrated stem-type w Grip Length: Between 0.469 inches and 0.532 inches Special Features: Single action fastener installed with a single action tool Material: Iron alloy 660 mechanical lock or steel comp 316 mechanical lockiron alloy 660 sleeveiron alloy 660 stem Material Specification: Arms 5737 assn standard 1st material response mechanical lock or arms 5690 assn standard 2nd material response mechanical lockams 5737 assn standard single material response stem Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A040a0 Mil-std (military Standard):	Self-plugging mechanically locked stem
Expansion Device: Serrated stem-type w Grip Length: Between 0.469 inches and 0.532 inches Special Features: Single action fastener installed with a single action tool Material: Iron alloy 660 mechanical lock or steel comp 316 mechanical lockiron alloy 660 sleeveiron alloy 660 stem Material Specification: Ams 5737 assn standard 1st material response mechanical lock or ams 5690 assn standard 2nd material response mechanical lockams 5737 assn standard single material response stem Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A040a0 Mil-std (military Standard):	Head Major Diameter:
Serrated stem-type w Grip Length: Between 0.469 inches and 0.532 inches Special Features: Single action fastener installed with a single action tool Material: Iron alloy 660 mechanical lock or steel comp 316 mechanical lockiron alloy 660 sleeveiron alloy 660 stem Material Specification: Ams 5737 assn standard 1st material response mechanical lock or ams 5690 assn standard 2nd material response mechanical lockams 5737 assn standard single material response sleeveams 5737 assn standard single material response stem Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A040a0 Mil-std (military Standard):	Between 0.400 inches and 0.432 inches
Grip Length: Between 0.469 inches and 0.532 inches Special Features: Single action fastener installed with a single action tool Material: Iron alloy 660 mechanical lock or steel comp 316 mechanical lockiron alloy 660 sleeveiron alloy 660 stem Material Specification: Ams 5737 assn standard 1st material response mechanical lock or ams 5690 assn standard 2nd material response mechanical lockams 5737 assn standard single material response sleeveams 5737 assn standard single material response stem Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Shelf Life: N/a Unit Of Measure: Demilitarization: No Filig: A040a0 Mil-std (military Standard):	Expansion Device:
Between 0.469 inches and 0.532 inches Special Features: Single action fastener installed with a single action tool Material: Iron alloy 660 mechanical lock or steel comp 316 mechanical lockiron alloy 660 sleeveiron alloy 660 stem Material Specification: Ams 5737 assn standard 1st material response mechanical lock or ams 5690 assn standard 2nd material response mechanical lockams 5737 assn standard single material response sleeveams 5737 assn standard single material response stem Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A040a0 Mil-std (military Standard):	Serrated stem-type w
Special Features: Single action fastener installed with a single action tool Material: Iron alloy 660 mechanical lock or steel comp 316 mechanical lockiron alloy 660 sleeveiron alloy 660 stem Material Specification: Ams 5737 assn standard 1st material response mechanical lock or ams 5690 assn standard 2nd material response mechanical lockams 5737 assn standard single material response stem Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A040a0 Mil-std (military Standard):	Grip Length:
Single action fastener installed with a single action tool Material: Iron alloy 660 mechanical lock or steel comp 316 mechanical lockiron alloy 660 sleeveiron alloy 660 stem Material Specification: Ams 5737 assn standard 1st material response mechanical lock or ams 5690 assn standard 2nd material response mechanical lockams 5737 assn standard single material response sleeveams 5737 assn standard single material response stem Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A040a0 Mil-std (military Standard):	Between 0.469 inches and 0.532 inches
Material: Iron alloy 660 mechanical lock or steel comp 316 mechanical lockiron alloy 660 sleeveiron alloy 660 stem Material Specification: Ams 5737 assn standard 1st material response mechanical lock or ams 5690 assn standard 2nd material response mechanical lockams 5737 assn standard single material response sleeveams 5737 assn standard single material response stem Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A040a0 Mil-std (military Standard):	Special Features:
Iron alloy 660 mechanical lock or steel comp 316 mechanical lockiron alloy 660 sleeveiron alloy 660 stem Material Specification: Ams 5737 assn standard 1st material response mechanical lock or ams 5690 assn standard 2nd material response mechanical lockams 5737 assn standard single material response stem Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Shelf Life: N/a Unit Of Measure: Demilitarization: No Filig: A040a0 Mil-std (military Standard):	Single action fastener installed with a single action tool
Material Specification: Ams 5737 assn standard 1st material response mechanical lock or ams 5690 assn standard 2nd material response mechanical lockame 5737 assn standard single material response stem Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A040a0 Mil-std (military Standard):	Material:
Ams 5737 assn standard 1st material response mechanical lock or ams 5690 assn standard 2nd material response mechanical lockams 5737 assn standard single material response stem Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A040a0 Mil-std (military Standard):	Iron alloy 660 mechanical lock or steel comp 316 mechanical lockiron alloy 660 sleeveiron alloy 660 stem
5737 assn standard single material response sleeveams 5737 assn standard single material response stem Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A040a0 Mil-std (military Standard):	Material Specification:
Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A040a0 Mil-std (military Standard):	Ams 5737 assn standard 1st material response mechanical lock or ams 5690 assn standard 2nd material response mechanical lockams
Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A040a0 Mil-std (military Standard):	5737 assn standard single material response sleeveams 5737 assn standard single material response stem
Surface Treatment Specification: Qq-p-35 federal specification single treatment response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A040a0 Mil-std (military Standard):	Surface Treatment:
Qq-p-35 federal specification single treatment response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A040a0 Mil-std (military Standard):	Passivate
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A040a0 Mil-std (military Standard):	Surface Treatment Specification:
N/a Unit Of Measure: Demilitarization: No Fiig: A040a0 Mil-std (military Standard):	Qq-p-35 federal specification single treatment response
Unit Of Measure: Demilitarization: No Fiig: A040a0 Mil-std (military Standard):	Shelf Life:
Demilitarization: No Fiig: A040a0 Mil-std (military Standard):	N/a
No Fiig: A040a0 Mil-std (military Standard):	Unit Of Measure:
No Fiig: A040a0 Mil-std (military Standard):	
Fiig: A040a0 Mil-std (military Standard):	Demilitarization:
A040a0 Mil-std (military Standard):	No
Mil-std (military Standard):	Fiig:
	A040a0
Mil-f-8975 spec.	Mil-std (military Standard):
	Mil-f-8975 spec.