NSN 5320-01-388-5020

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-388-5020 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.785 inches and 0.825 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.791 inches and 0.806 inches **Shank Diameter:** Between 0.188 inches and 0.189 inches Shank Style: **Head Major Diameter:** 0.305 inches Lubrication: Cetyl alcohol **Grip Length:** Between 0.439 inches and 0.500 inches **Thread Size:** 0.190 inches **Shear Strength:** 156000 single pounds per square inch **Countersink Angle:** 101.0 degrees Material: Steel comp h11 **Material Specification:** Ams 6485 assn standard single material response **Surface Treatment:** Nickel and cadmium **Surface Treatment Specification:** Ams 2416 assn standard single treatment response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas4452 professional/industrial association standard Shelf Life: N/a **Unit Of Measure:**

--

NSN 5320-01-388-5020

Pin-rivet - Page 2 of 2



_		••	• •				
וו	em	ш	112	rız	211	n	٠.

No

Fiig:

A528u0