

View Online at <https://aerobasegroup.com/nsn/5320-01-388-9079>

Thread Class:

3a

Thread Direction:

Right-hand

Identification Code Color:

Bronze

Fastener Length:

Between 0.707 inches and 0.727 inches

Head Style:

Flush countersunk

Width Between Flats:

Between 0.0791 inches and 0.0801 inches

Shank Diameter:

Between 0.1625 inches and 0.1635 inches

Shank Style:

Head Major Diameter:

Between 0.2564 inches and 0.2612 inches

End Application:

W/s: aircraft, (ac-130h, mc-130h, ec-130e, hc-130)

Grip Length:

Between 0.370 inches and 0.380 inches

Min. Tensile Strength (psi):

160000 pounds per square inch

Thread Size:

0.164 inches

Countersink Angle:

100.0 degrees

Material:

Steel comp e4340 or steel comp 8640 or steel comp 4140

Material Specification:

Mil-s-5000 military specification single material response or mil-s-5626 military specification single material response or mil-s-6049 military specification single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type ii, class 3 federal specification single treatment response

Thread Series Designator:

Unjc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-5000 spec.