

View Online at <https://aerobasegroup.com/nsn/5320-01-388-9101>

Thread Class:

3a

Thread Direction:

Right-hand

Identification Code Color:

Bronze

Fastener Length:

Between 0.894 inches and 0.914 inches

Head Style:

Straight pan

Head Height:

Between 0.037 inches and 0.047 inches

Shank Diameter:

Between 0.162 inches and 0.163 inches

Shank Style:

Pin-riquet, tapered, threaded

Head Major Diameter:

Between 0.242 inches and 0.262 inches

Tip Diameter:

Between 0.157 inches and 0.159 inches

Grip Length:

Between 0.557 inches and 0.567 inches

Min. Tensile Strength (psi):

1940 pounds per square inch

Thread Size:

0.164 inches

Shear Strength:

4010 double pounds per square inch

Material:

Steel comp e4340 or steel comp 4140

Material Specification:

Mil-s-5000 military specification single material response or mil-s-5626 military specification single material response

Surface Treatment:

Cadmium or chromate

Surface Treatment Specification:

Qq-p-416 federal specification single treatment response

Thread Series Designator:

Unjc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-5000 spec.