## NSN 5320-01-389-0045

Solid Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-389-0045

Fastener Length:
Between 0.178 inches and 0.198 inches
Head Style:
Undersized oval countersunk
Head Height:
Between 0.003 inches and 0.005 inches
Shank Diameter:
Between 0.124 inches and 0.127 inches
Shank Style:
Straight w/radius chamfered tip
Head Major Diameter:
0.1742 inches
Head Minor Diameter:
0.134 mils and 0.144 centimeters
Countersink Height:
0.0286 inches
Shear Strength:
26000 single pounds per square inch
Countersink Angle:
Between 70.0 degrees and 130.0 degrees
Heat Treatment:
T-4 solution heat treated
Material:
Aluminum alloy 2117
Material Specification:
Qq-a-430 federal specification single material response or ams 4982 assn standard single material response
Surface Treatment:
Anodize
Surface Treatment Specification:
Mil-a-8625, type ii, class 1, clear military specification single treatment response
Specification Data:
80205-nas1097 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig:
A040a0
Mil-std (military Standard):
Mil-a-8625 spec.