## NSN 5320-01-389-6341

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-389-6341 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.203 inches and 1.223 inches **Head Style:** Err-090 **Head Height:** Between 0.059 inches and 0.069 inches Width Between Flats: Between 0.0947 inches and 0.0967 inches **Shank Diameter:** Between 0.2696 inches and 0.2701 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.387 inches and 0.412 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corporation and dry film and solid film **Grip Length:** Between 0.678 inches and 0.698 inches **Thread Size:** 0.250 inches **Shear Strength:** 95000 single pounds per square inch **Special Features:** 1/64 oversized. For repair use only. Material: Titanium alloy uns r56400 **Material Specification:** Ams4928 assn standard single material response or ams4967 assn standard single material response **Surface Treatment:** Anodize **Thread Series Designator:** Unjf **Specification Data:** 26512-gb511be manufacturers specification control Shelf Life: N/a

**Unit Of Measure:** 

## NSN 5320-01-389-6341

Pin-rivet - Page 2 of 2



Demilitarization:

No

Fiig:

A528u0