NSN 5320-01-389-7584

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-389-7584

Fastener Length:

0.844 inches

Head Style:

Tapered pan

Head Height:

Between 0.130 inches and 0.140 inches

Shank Diameter:

Between 0.250 inches and 0.260 inches

Shank Style:

Self-plugging mechanically locked stem

Head Major Diameter:

Between 0.400 inches and 0.432 inches

Expansion Device:

Serrated stem-type w

Grip Length:

Between 0.594 inches and 0.657 inches

Special Features:

Single action fastener installed with a single action tool

Material:

Iron alloy 660 mechanical lock or steel comp 316 mechanical lockiron alloy 660 sleeveiron alloy 660 stem

Material Specification:

Ams 5737 assn standard 1st material response mechanical lock or ams 5690 assn standard 2nd material response mechanical lockams

5737 assn standard single material response sleeveams 5737 assn standard single material response stem

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-f-8975 spec.