## NSN 5320-01-390-3826

Pin-rivet - Page 1 of 2

**Thread Class:** 

Right-hand

Green

**Thread Direction:** 

Fastener Length:

**Identification Code Color:** 

Between 1.073 inches and 1.093 inches

За



View Online at https://aerobasegroup.com/nsn/5320-01-390-3826

Head Style:
Err-090
Head Height:
Between 0.080 inches and 0.090 inches
Width Between Flats:
Between 0.0947 inches and 0.0967 inches
Shank Diameter:
Between 0.2485 inches and 0.2495 inches
Shank Style:
Pin-rivet, straight, threaded
Head Major Diameter:
Between 0.415 inches and 0.440 inches
Lubrication:
Cetyl alcohol
Grip Length:
Between 0.683 inches and 0.693 inches
Min. Tensile Strength (psi):
7750 pounds per square inch
Hardness Rating:
50.0 rockwell a head and 80.0 rockwell a head
Thread Size:
0.250 inches
Shear Strength:
12260 double pounds per square inch
Special Features:
Top of head shall be powder blasted
Material:
Nickel alloy 718
Material Specification:
Ams5662 assn standard single material response
Thread Series Designator:
Unjf
Specification Data:
76823-03a064 manufacturers standard

## NSN 5320-01-390-3826

Pin-rivet - Page 2 of 2



_				
c	hο	JIF.		ife:
J			_	HG.

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A528u0