

View Online at <https://aerobasegroup.com/nsn/5320-01-390-4205>

Thread Class:

3a

Thread Direction:

Right-hand

Identification Code Color:

Green

Fastener Length:

Between 0.503 inches and 0.523 inches

Head Style:

Flush countersunk

Width Between Flats:

Between 0.0791 inches and 0.0801 inches

Shank Diameter:

Between 0.1890 inches and 0.1895 inches

Shank Style:

Pin-riquet, straight, threaded

Head Major Diameter:

Between 0.3765 inches and 0.3813 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

Grip Length:

Between 0.183 inches and 0.193 inches

Min. Tensile Strength (psi):

4350 pounds per square inch

Thread Size:

0.190 inches

Shear Strength:

7060 double pounds per square inch

Countersink Angle:

100.0 degrees

Special Features:

Grit blast top of head, with color green on thread end.

Material:

Nickel alloy 718

Material Specification:

Ams5662 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Hi-shear spec. 258, 73197 mfr ref single treatment response

Thread Series Designator:

Unjf

Specification Data:

73197-hlt423 manufacturers standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A528u0