## NSN 5320-01-390-4216

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-390-4216 **Thread Class:** За **Thread Direction:** Right-hand **Identification Code Color:** Blue **Fastener Length:** Between 1.885 inches and 1.905 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.252 inches and 0.255 inches **Shank Diameter:** Between 0.5610 inches and 0.5615 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 1.133 inches and 1.140 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** Between 1.115 inches and 1.135 inches Min. Tensile Strength (psi): 32400 pounds per square inch **Thread Size:** 0.916 inches **Shear Strength:** 47200 double pounds per square inch **Countersink Angle:** 100.0 degrees **Special Features:** Grit blast top of head Material: Titanium alloy uns r56400 **Material Specification:** Ams 4928 assn standard single material response **Thread Series Designator:** Unjf Shelf Life: N/a

--

**Unit Of Measure:** 

## NSN 5320-01-390-4216

Pin-rivet - Page 2 of 2



em			

No

Fiig:

A528u0