## NSN 5320-01-390-4217

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-390-4217 **Thread Class:** За **Thread Direction:** Right-hand **Identification Code Color:** Blue **Fastener Length:** Between 1.760 inches and 1.780 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.252 inches and 0.255 inches **Shank Diameter:** 0.561 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 1.133 inches and 1.140 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** Between 0.995 inches and 1.005 inches Min. Tensile Strength (psi): 32400 pounds per square inch **Thread Size:** 0.562 inches **Shear Strength:** 47200 double pounds per square inch **Countersink Angle:** 100.0 degrees **Special Features:** Grit blast top of head Material: Titanium alloy uns r56400 **Material Specification:** Ams 4928 assn standard single material response

Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
--

## NSN 5320-01-390-4217

Pin-rivet - Page 2 of 2



_		••	• •				
וו	em	ш	112	rız	211	n	٠.

No

Fiig:

A528u0