NSN 5320-01-390-5208

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-390-5208
Thread Class:
3a
Thread Direction:
Right-hand
Identification Code Color:
Blue
Fastener Length:
Between 1.698 inches and 1.718 inches
Head Style:
Flush countersunk
Width Between Flats:
Between 0.2520 inches and 0.2555 inches
Shank Diameter:
Between 0.5610 inches and 0.5615 inches
Shank Style:
Pin-rivet, straight, threaded
Head Major Diameter:
Between 1.1337 inches and 1.1408 inches
Lubrication:
Cetyl alcohol, specification 305, hi-shear corp
Grip Length:
Between 0.933 inches and 0.943 inches
Min. Tensile Strength (psi):
32400 pounds per square inch
Thread Size:
0.562 inches
Shear Strength:
47200 double pounds per square inch
Countersink Angle:
100.0 degrees
Special Features:
Grit blast top of head, with light blue on thread end.
Material:
Titanium alloy uns r56400
Material Specification:
Ams 4928 assn standard single material response or ams 4967 assn standard single material response
Thread Series Designator:
Unjf
Specification Data:
73197-hlt453 manufacturers standard
Shelf Life:

N/a

NSN 5320-01-390-5208

Pin-rivet - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A528u0