

View Online at <https://aerobasegroup.com/nsn/5320-01-390-7083>

Thread Class:

3a

Thread Direction:

Right-hand

Identification Code Color:

Blue

Fastener Length:

Between 0.885 inches and 0.905 inches

Head Style:

Flush countersunk

Width Between Flats:

Between 0.0947 inches and 0.0967 inches

Shank Diameter:

Between 0.2490 inches and 0.2495 inches

Shank Style:

Pin-riquet, straight, threaded

Head Major Diameter:

Between 0.3898 inches and 0.3948 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

Grip Length:

Between 0.495 inches and 0.505 inches

Min. Tensile Strength (psi):

4400 pounds per square inch

Thread Size:

0.250 inches

Shear Strength:

12260 double pounds per square inch

Countersink Angle:

100.0 degrees

Special Features:

Light blue color identification on top of head.

Material:

Nickel alloy 718

Material Specification:

Ams5662 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Hi-shear spec. 258, 73197 mfr ref single treatment response

Thread Series Designator:

Unjf

Specification Data:

26512-gb510ff manufacturers specification control

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0