NSN 5320-01-390-7135

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-390-7135 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.107 inches and 1.127 inches **Head Style:** Err-090 **Head Height:** Between 0.130 inches and 0.140 inches **Shank Diameter:** Between 0.373 inches and 0.374 inches **Shank Style:** Pin-rivet, tapered, threaded **Head Major Diameter:** Between 0.586 inches and 0.600 inches Tip Diameter: Between 0.130 inches and 0.140 inches Lubrication: Cetyl alcohol **Grip Length:** Between 0.620 inches and 0.630 inches Min. Tensile Strength (psi): 19100 pounds per square inch **Thread Size:** 0.375 inches **Shear Strength:** 27600 double pounds per square inch Material: Nickel alloy k-500 **Material Specification:** Ams 5662 assn standard single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

--

Unit Of Measure:

NSN 5320-01-390-7135

Pin-rivet - Page 2 of 2



_		••	• •				
וו	em	ш	112	rız	211	n	٠.

No

Fiig:

A528u0