## NSN 5320-01-390-7138

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-390-7138 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 2.010 inches and 2.030 inches **Head Style:** Err-090 **Head Height:** Between 0.080 inches and 0.090 inches **Shank Diameter:** 0.250 inches **Shank Style:** Pin-rivet, tapered, threaded **Head Major Diameter:** Between 0.415 inches and 0.440 inches Tip Diameter: Between 0.241 inches and 0.244 inches Lubrication: Cetyl alcohol **Grip Length:** Between 1.620 inches and 1.630 inches Min. Tensile Strength (psi): 7750 pounds per square inch **Thread Size:** 0.250 inches **Shear Strength:** 12260 double pounds per square inch Material: Nickel alloy k-500 **Material Specification:** Ams 5662 assn standard single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416 type 2 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

--

**Unit Of Measure:** 

## NSN 5320-01-390-7138

Pin-rivet - Page 2 of 2



em			

No

Fiig:

A528u0