NSN 5320-01-390-8375



Pin-rivet - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5320-01-390-8375 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.198 inches and 1.218 inches **Head Style:** Err-090 **Head Height:** Between 0.010 inches and 0.015 inches Width Between Flats: Between 0.122 inches and 0.142 inches **Shank Diameter:** Between 0.2490 inches and 0.2495 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.3898 inches and 0.3948 inches **Head Minor Diameter:** Between 0.375 inches and 0.388 inches **Countersink Height:** Between 0.0600 inches and 0.0625 inches Lubrication: Solid film and cetyl alcohol **End Application:** C-17 **Grip Length:** Between 0.807 inches and 0.817 inches Thready Qty Per Inch (tpi): 28 **Thread Size:**

0.250 inches

Countersink Angle:

100.0 degrees

Product Name:

Pin-rivet, threaded

Material:

Titanium alloy uns r56400

Material Specification:

Ams4967 assn standard single material response or ams4928 assn standard single material response

Thread Series Designator:

Unjf

NSN 5320-01-390-8375

Pin-rivet - Page 2 of 2



Spec	ifi	cation	Data
------	-----	--------	------

88277-3d0098 manufacturers standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0