# NSN 5320-01-390-8378

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-390-8378



# Thread Class:

3a

**Thread Direction:** 

**Right-hand** 

### Fastener Length:

Between 2.063 inches and 2.093 inches

# Head Style:

Err-090

#### Head Height:

Between 0.160 inches and 0.180 inches

#### Shank Diameter:

Between 0.437 inches and 0.438 inches

#### Shank Style:

Pin-rivet, tapered, threaded

#### Head Major Diameter:

Between 0.641 inches and 0.679 inches

#### **Tip Diameter:**

Between 0.431 inches and 0.434 inches

#### Lubrication:

Cetyl alcohol

## Grip Length:

Between 1.433 inches and 1.443 inches

#### Min. Tensile Strength (psi):

25800 pounds per square inch

#### Thread Size:

0.438 inches

#### Shear Strength:

37500 double pounds per square inch

#### Material:

Nickel alloy k-500

#### **Material Specification:**

Ams 5662 assn standard single material response

#### Surface Treatment:

Passivate

### **Thread Series Designator:**

Unjf

## Shelf Life:

N/a

#### Unit Of Measure:

---

# Demilitarization:

No

# NSN 5320-01-390-8378

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

