## NSN 5320-01-390-8379

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-390-8379



**Thread Class:** 

3a

**Thread Direction:** 

**Right-hand** 

Fastener Length:

Between 1.974 inches and 1.994 inches

Head Style:

Err-090

Head Height:

Between 0.130 inches and 0.140 inches

Shank Diameter:

Between 0.373 inches and 0.374 inches

Shank Style:

Pin-rivet, tapered, threaded

Head Major Diameter:

Between 0.585 inches and 0.600 inches

**Tip Diameter:** 

Between 0.364 inches and 0.368 inches

Lubrication:

Cetyl alcohol

Grip Length:

Between 1.433 inches and 1.443 inches

Min. Tensile Strength (psi):

19100 pounds per square inch

**Thread Size:** 

0.375 inches

Shear Strength:

27600 double pounds per square inch

Material:

Nickel alloy k-500

Material Specification:

Ams 5662 assn standard single material response

**Surface Treatment:** 

Passivate

**Thread Series Designator:** 

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

## NSN 5320-01-390-8379

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

