NSN 5320-01-390-8501

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-390-8501



Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 1.428 inches and 1.448 inches

Head Style:

Err-090

Head Height:

Between 0.102 inches and 0.112 inches

Shank Diameter:

Between 0.311 inches and 0.312 inches

Shank Style:

Pin-rivet, tapered, threaded

Head Major Diameter:

Between 0.476 inches and 0.506 inches

Tip Diameter:

Between 0.308 inches and 0.309 inches

Lubrication:

Cetyl alcohol

Grip Length:

Between 0.933 inches and 0.943 inches

Min. Tensile Strength (psi):

12300 pounds per square inch

Thread Size:

0.312 inches

Shear Strength:

19160 double pounds per square inch

Material:

Nickel alloy k-500

Material Specification:

Ams 5662 assn standard single material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

NSN 5320-01-390-8501

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

