## NSN 5320-01-390-8501

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-390-8501 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.428 inches and 1.448 inches **Head Style:** Err-090 **Head Height:** Between 0.102 inches and 0.112 inches **Shank Diameter:** Between 0.311 inches and 0.312 inches **Shank Style:** Pin-rivet, tapered, threaded **Head Major Diameter:** Between 0.476 inches and 0.506 inches Tip Diameter: Between 0.308 inches and 0.309 inches Lubrication: Cetyl alcohol **Grip Length:** Between 0.933 inches and 0.943 inches Min. Tensile Strength (psi): 12300 pounds per square inch **Thread Size:** 0.312 inches **Shear Strength:** 19160 double pounds per square inch Material: Nickel alloy k-500 **Material Specification:** Ams 5662 assn standard single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

--

**Unit Of Measure:** 

## NSN 5320-01-390-8501

Pin-rivet - Page 2 of 2



_		••	• •					
וו	em	ш	112	r17	2+	$\sim$	n	
$\boldsymbol{-}$	CIII	••	ıιa	114	.aı	ı		

No

Fiig:

A528u0