NSN 5320-01-390-8507

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-390-8507



Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 1.197 inches and 1.217 inches

Head Style:

Err-090

Head Height:

Between 0.080 inches and 0.090 inches

Shank Diameter:

Between 0.248 inches and 0.249 inches

Shank Style:

Pin-rivet, tapered, threaded

Head Major Diameter:

Between 0.415 inches and 0.440 inches

Tip Diameter:

Between 0.241 inches and 0.244 inches

Lubrication:

Cetyl alcohol

Grip Length:

Between 0.807 inches and 0.817 inches

Min. Tensile Strength (psi):

7750 pounds per square inch

Thread Size:

0.250 inches

Shear Strength:

12260 double pounds per square inch

Material:

Nickel alloy k-500

Material Specification:

Ams 5662 assn standard single material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

NSN 5320-01-390-8507

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

