## NSN 5320-01-390-8514

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-390-8514

Thread Class:
3a
Thread Direction:
Right-hand
Fastener Length:
Between 1.535 inches and 1.555 inches
Head Style:
Err-090
Head Height:
Between 0.010 inches and 0.015 inches
Width Between Flats:
Between 0.197 inches and 0.217 inches
Shank Diameter:
Between 0.3740 inches and 0.3745 inches
Shank Style:
Pin-rivet, straight, threaded
Head Major Diameter:
Between 0.5554 inches and 0.5604 inches
Head Minor Diameter:
Between 0.541 inches and 0.554 inches
Countersink Height:
Between 0.770 inches and 0.795 inches
Lubrication:
Cetyl alcohol and solid film
End Application:
C-17
Grip Length:
Between 0.995 inches and 1.005 inches
Thready Qty Per Inch (tpi):
24
Thread Size:
0.375 inches
Countersink Angle:
100.0 degrees
Product Name:
Pin-rivet, threaded
Material:
Titanium alloy uns r56400
Material Specification:
Ams4967 assn standard single material response or ams4928 assn standard single material response
Thread Series Designator:

Unjf

## NSN 5320-01-390-8514

Pin-rivet - Page 2 of 2



Spec	ifi	cation	Data
------	-----	--------	------

88277-3d0098 manufacturers standard

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A528u0