NSN 5320-01-390-8516



Pin-rivet - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5320-01-390-8516 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.785 inches and 1.805 inches **Head Style:** Err-090 **Head Height:** Between 0.010 inches and 0.015 inches Width Between Flats: Between 0.197 inches and 0.217 inches **Shank Diameter:** Between 0.3740 inches and 0.3745 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.5554 inches and 0.5604 inches **Head Minor Diameter:** Between 0.541 inches and 0.554 inches **Countersink Height:** Between 0.770 inches and 0.795 inches Lubrication: Cetyl alcohol and solid film **End Application:** C-17 **Grip Length:** Between 1.245 inches and 1.255 inches Thready Qty Per Inch (tpi): 24 **Thread Size:** 0.375 inches **Countersink Angle:** 100.0 degrees **Product Name:** Pin-rivet, threaded Material: Titanium alloy uns r56400 **Material Specification:** Ams4967 assn standard single material response or ams4928 assn standard single material response

Unjf

Thread Series Designator:

NSN 5320-01-390-8516

Pin-rivet - Page 2 of 2



~n	ΔC IT	100	HINE	1 1 1	212
JU	CUII	166	ıtior	·	ala.

88277-3d0098 manufacturers standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0