

View Online at <https://aerobasegroup.com/nsn/5320-01-390-8518>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.677 inches and 0.697 inches

Head Style:

Err-090

Head Height:

Between 0.010 inches and 0.015 inches

Width Between Flats:

Between 0.094 inches and 0.104 inches

Shank Diameter:

Between 0.1635 inches and 0.1640 inches

Shank Style:

Pin-riquet, straight, threaded

Head Major Diameter:

Between 0.2564 inches and 0.2612 inches

Head Minor Diameter:

Between 0.241 inches and 0.254 inches

Countersink Height:

Between 0.0400 inches and 0.0425 inches

Lubrication:

Cetyl alcohol

End Application:

C-17

Grip Length:

Between 0.370 inches and 0.380 inches

Thread Size:

0.164 inches

Countersink Angle:

100.0 degrees

Product Name:

Pin-riquet, threaded

Material:

Titanium alloy uns r56400

Material Specification:

Ams4967 assn standard single material response or ams4928 assn standard single material response

Surface Treatment:

Aluminum

Surface Treatment Specification:

Hi-shear spec.No.29 (hi-kote 1 only) mfr ref single treatment response

Thread Series Designator:

Unjc

Specification Data:

88277-3d0098 manufacturers standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0