NSN 5320-01-390-8518

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-390-8518 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.677 inches and 0.697 inches **Head Style:** Err-090 **Head Height:** Between 0.010 inches and 0.015 inches Width Between Flats: Between 0.094 inches and 0.104 inches **Shank Diameter:** Between 0.1635 inches and 0.1640 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.2564 inches and 0.2612 inches **Head Minor Diameter:** Between 0.241 inches and 0.254 inches **Countersink Height:** Between 0.0400 inches and 0.0425 inches Lubrication: Cetyl alcohol **End Application:** C-17 **Grip Length:** Between 0.370 inches and 0.380 inches **Thread Size:** 0.164 inches **Countersink Angle:** 100.0 degrees **Product Name:** Pin-rivet, threaded Material: Titanium alloy uns r56400 **Material Specification:** Ams4967 assn standard single material response or ams4928 assn standard single material response **Surface Treatment:**

Aluminum

Surface Treatment Specification:

Hi-shear spec.No.29 (hi-kote 1 only) mfr ref single treatment response

NSN 5320-01-390-8518

Pin-rivet - Page 2 of 2



Thread Series Designator:
Unjc
Specification Data:
88277-3d0098 manufacturers standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A528u0