## NSN 5320-01-390-9052

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-390-9052

Thread C	lass:
----------	-------

3a

**Thread Direction:** 

**Right-hand** 

### Fastener Length:

0.625 inches

#### **Head Style:**

Flush countersunk

#### Width Between Flats:

Between 0.0535 inches and 0.0540 inches

Shank Diameter:

0.2612 inches

Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

0.2612 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

#### Grip Length:

0.312 inches

## Thread Size:

0.158 inches

## Shear Strength:

85000 single pounds per square inch

#### **Countersink Angle:**

100.0 degrees

#### **Special Features:**

Furnished w/ undersize threads

#### Material:

Iron alloy 660

#### **Material Specification:**

Ams5731 assn standard single material response or ams5737 assn standard single material response

#### Surface Treatment:

Passivate

#### Surface Treatment Specification:

Hi-shear no. 358 mfr ref single treatment response

## **Thread Series Designator:**

Unjf

Shelf Life:

N/a

#### Unit Of Measure:

---

# NSN 5320-01-390-9052

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

