

View Online at <https://aerobasegroup.com/nsn/5320-01-391-0411>

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 22.00 millimeters and 22.90 millimeters

**Head Style:**

Flush countersunk

**Shank Diameter:**

Between 4.978 millimeters and 4.990 millimeters

**Shank Style:**

Pin-riquet, straight, threaded

**Head Major Diameter:**

Between 7.71 millimeters and 7.85 millimeters

**Lubrication:**

Cetyl alcohol, specification 305, hi-shear corp

**Grip Length:**

Between 14.87 millimeters and 15.13 millimeters

**Thready Qty Per Inch (tpi):**

0.80

**Min. Tensile Strength (psi):**

9300 newtons per square millimeter

**Thread Size:**

5.0 millimeters

**Shear Strength:**

25700 double newtons per square millimeter

**Countersink Angle:**

Between 99.0 degrees and 100.0 degrees

**Thread Tolerance Class:**

4h external

**Material:**

Titanium alloy

**Material Specification:**

Ams4298 assn standard single material response or ams4967 assn standard single material response

**Thread Series Designator:**

Iso m

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A528u0