

View Online at <https://aerobasegroup.com/nsn/5320-01-391-1375>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

1.490 inches

**Head Style:**

Flush countersunk

**Width Between Flats:**

Between 0.1270 inches and 0.1295 inches

**Shank Diameter:**

Between 0.3115 inches and 0.3120 inches

**Shank Style:**

**Head Major Diameter:**

Between 0.531 inches and 0.561 inches

**Lubrication:**

Cetyl alcohol

**Grip Length:**

Between 0.939 inches and 1.000 inches

**Min. Tensile Strength (psi):**

7100 pounds per square inch

**Thread Size:**

0.312 inches

**Shear Strength:**

14600 double pounds per square inch

**Countersink Angle:**

100.0 degrees

**Material:**

Iron alloy 660

**Material Specification:**

Ams5731 assn standard single material response or ams5737 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Specification Data:**

88277-3d0008 manufacturers standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0