## NSN 5320-01-391-1375

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-391-1375

Thread Class:

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

1.490 inches

#### Head Style:

Flush countersunk

## Width Between Flats:

Between 0.1270 inches and 0.1295 inches

Shank Diameter:

Between 0.3115 inches and 0.3120 inches

Shank Style:

#### Head Major Diameter:

Between 0.531 inches and 0.561 inches

Lubrication:

Cetyl alcohol

#### Grip Length:

Between 0.939 inches and 1.000 inches

### Min. Tensile Strength (psi):

7100 pounds per square inch

## Thread Size:

0.312 inches

#### Shear Strength:

14600 double pounds per square inch

#### **Countersink Angle:**

100.0 degrees

#### Material:

Iron alloy 660

#### **Material Specification:**

Ams5731 assn standard single material response or ams5737 assn standard single material response

#### Surface Treatment:

Passivate

#### Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

#### **Thread Series Designator:**

Unjf

## Specification Data:

88277-3d0008 manufacturers standard

## Shelf Life:

N/a

# NSN 5320-01-391-1375

Pin-rivet - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A528u0

