

View Online at <https://aerobasegroup.com/nsn/5320-01-391-1578>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 1.535 inches and 1.555 inches

Head Style:

Flush countersunk

Head Height:

Between 0.1600 inches and 0.1620 inches

Width Between Flats:

Between 0.1582 inches and 0.1617 inches

Shank Diameter:

Between 0.3740 inches and 0.3745 inches

Shank Style:

Pin-riquet, straight, threaded

Head Major Diameter:

Between 0.7556 inches and 0.7604 inches

Lubrication:

Cetyl alcohol

End Application:

C-17

Grip Length:

Between 0.995 inches and 1.005 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

210000 pounds per square inch

Thread Size:

0.3750 inches

Shear Strength:

27600 double pounds per square inch

Countersink Angle:

100.0 degrees

Material:

Nickel alloy 718

Material Specification:

Ams 5662 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Hi-shear specification 258 mfr ref single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0