NSN 5320-01-391-2232

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-391-2232 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: 2.082 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.0947 inches and 0.0967 inches **Shank Diameter:** Between 0.2490 inches and 0.2495 inches **Shank Style: Head Major Diameter:** Between 0.3898 inches and 0.3948 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** 1.6875 inches **Thread Size:** 0.2425 inches **Shear Strength:** 85000 single pounds per square inch **Countersink Angle:** 100.0 degrees **Special Features:** Furnished w/ undersize thd dia Material: Iron alloy 660 **Material Specification:** Ams5731 assn standard single material response or ams5737 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Hi-shear no. 358 mfr ref single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

Unit Of Measure:

NSN 5320-01-391-2232

Pin-rivet - Page 2 of 2



Demilitarization:

No

Fiig:

A528u0