## NSN 5320-01-391-2233

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-391-2233 **Thread Class:** АЗа **Thread Direction:** Right-hand Fastener Length: 0.888 inches **Head Style:** Flush countersunk Width Between Flats: 0.080 inches **Shank Diameter:** Between 0.1890 inches and 0.1895 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** 0.300 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** 0.562 inches **Thread Size:** 0.1825 inches **Shear Strength:** 85000 single pounds per square inch **Countersink Angle:** 100.0 degrees **Special Features:** Furnished w/ undersize thd dia Material: Iron alloy 660 **Material Specification:** Ams5731 assn standard single material response or ams5737 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Hi-shear no. 358 mfr ref single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

**Unit Of Measure:** 

## NSN 5320-01-391-2233

Pin-rivet - Page 2 of 2



_		••	• •				
וו	em	ш	112	rız	211	n	٠.

No

Fiig:

A528u0