

View Online at <https://aerobasegroup.com/nsn/5320-01-391-2252>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 1.285 inches and 1.305 inches

Head Style:

Err-090

Head Height:

Between 0.010 inches and 0.015 inches

Width Between Flats:

Between 0.197 inches and 0.217 inches

Shank Diameter:

Between 0.3740 inches and 0.3745 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.5554 inches and 0.5604 inches

Head Minor Diameter:

Between 0.541 inches and 0.554 inches

Countersink Height:

Between 0.770 inches and 0.795 inches

Lubrication:

Cetyl alcohol and solid film

End Application:

C-17

Grip Length:

Between 0.745 inches and 0.755 inches

Thready Qty Per Inch (tpi):

24

Thread Size:

0.375 inches

Countersink Angle:

100.0 degrees

Product Name:

Pin-rivet, threaded

Material:

Titanium alloy uns r56400

Material Specification:

Ams4967 assn standard single material response or ams4928 assn standard single material response

Thread Series Designator:

Unjf

Specification Data:

88277-3d0098 manufacturers standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0