

View Online at <https://aerobasegroup.com/nsn/5320-01-391-2308>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 1.378 inches and 1.398 inches

Head Style:

Err-090

Head Height:

Between 0.010 inches and 0.015 inches

Width Between Flats:

Between 0.0791 inches and 0.0806 inches

Shank Diameter:

Between 0.1890 inches and 0.1895 inches

Shank Style:

Head Major Diameter:

Between 0.3486 inches and 0.3536 inches

Head Minor Diameter:

Between 0.334 inches and 0.347 inches

Countersink Height:

Between 0.0667 inches and 0.0688 inches

Lubrication:

Solid film

End Application:

C-17

Grip Length:

Between 1.058 inches and 1.068 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

160000 pounds per square inch

Thread Size:

0.190 inches

Shear Strength:

95000 single pounds per square inch

Countersink Angle:

100.0 degrees

Product Name:

Pin-rivet, threaded

Material:

Titanium alloy uns r56400

Material Specification:

Ams 4967 assn standard single material response or ams 4928 assn standard single material response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0