NSN 5320-01-391-2308

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-391-2308 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.378 inches and 1.398 inches **Head Style:** Err-090 **Head Height:** Between 0.010 inches and 0.015 inches Width Between Flats: Between 0.0791 inches and 0.0806 inches **Shank Diameter:** Between 0.1890 inches and 0.1895 inches **Shank Style: Head Major Diameter:** Between 0.3486 inches and 0.3536 inches **Head Minor Diameter:** Between 0.334 inches and 0.347 inches **Countersink Height:** Between 0.0667 inches and 0.0688 inches Lubrication: Solid film **End Application:** C-17 **Grip Length:** Between 1.058 inches and 1.068 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Thread Size:** 0.190 inches 95000 single pounds per square inch

Shear Strength: Countersink Angle: 100.0 degrees **Product Name:** Pin-rivet, threaded Material: Titanium alloy uns r56400

NSN 5320-01-391-2308

Pin-rivet - Page 2 of 2



| N | Iэ | tωr | ial | Q | nΔ | cif | ic | ati | ۸r | ٠. |
|---|----|-----|-----|---|----|-----|----|-----|-----|----|
| ľ | ıa | rei | ıaı | · | ԻԲ | UII | ľ | au | VI. | ١. |

Ams 4967 assn standard single material response or ams 4928 assn standard single material response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0